

2SC4154

FOR LOW FREQUENCY AMPLIFY APPLICATION
SILICON NPN EPITAXIAL TYPE

DESCRIPTION

2SC4154 is a mini package resin sealed silicon NPN epitaxial transistor, It is designed for low frequency voltage application.

FEATURE



- Small collector to emitter saturation voltage.
 $V_{CE(sat)}=0.3V \text{ max (@}I_C=100mA/I_B=10mA)$
- Excellent linearity of DC forward current gain.
- Super mini package for easy mounting

APPLICATION

For Hybrid IC, Small type machine low frequency voltage amplify application.

OUTLINE DRAWING

Unit:mm




Terminal Connector JEITA: SC-70
①: Base JEDEC: -
②: Emitter
③: Collector

MAXIMUM RATINGS ($T_a=25^\circ\text{C}$)

Parameter	Symbol	Ratings	Unit
Collector to Base voltage	V_{CBO}	50	V
Emitter to Base voltage	V_{EBO}	6	V
Collector to Emitter voltage	V_{CEO}	50	V
Collector current	I_C	200	mA
Collector dissipation	P_C	200	mW
Junction temperature	T_j	+150	$^\circ\text{C}$
Storage temperature	T_{stg}	-55~+150	$^\circ\text{C}$

MARKING



ELECTRICAL CHARACTERISTICS ($T_a=25^\circ\text{C}$)

Parameter	Symbol	Test conditions	Limits			Unit
			Min	Typ	Max	
C to E breakdown voltage	$V_{(BR)CEO}$	$I_C=100 \mu A, R_{BE}=\infty$	50	-	-	V
Collector cut off current	I_{CBO}	$V_{CB}=50V, I_E=0mA$	-	-	0.1	μA
Emitter cut off current	I_{EBO}	$V_{EB}=6V, I_C=0mA$	-	-	0.1	μA
DC forward current gain ※	hFE	$V_{CE}=6V, I_C=1mA$	150	-	500	-
DC forward current gain	hFE	$V_{CE}=6V, I_C=0.1mA$	90	-	-	-
C to E Saturation voltage	$V_{CE(sat)}$	$I_C=100mA, I_B=10mA$	-	-	0.3	V
Gain bandwidth product	f_T	$V_{CE}=6V, I_E=-10mA$	-	200	-	MHz
Collector output capacitance	C_{ob}	$V_{CB}=6V, I_E=0, f=1MHz$	-	2.5	-	pF
Noise figure	NF	$V_{CE}=6V, I_E=-0.1mA, f=1kHz, R_G=2k\Omega$	-	-	15	dB







※) It shows hFE classification at right table.

Item	E	F
hFE	150~300	250~500

2SC4154

FOR LOW FREQUENCY AMPLIFY APPLICATION
SILICON NPN EPITAXIAL TYPE


TYPICAL CHARACTERISTICS




2SC4154

FOR LOW FREQUENCY AMPLIFY APPLICATION
SILICON NPN EPITAXIAL TYPE

Pc-Ta



ASO



Keep safety first in your circuit designs!

·ISAHAYA Electronics Corporation puts the maximum effort into making semiconductor products better and more reliable, but there is always the possibility that trouble may occur with them. Trouble with semiconductors may lead to personal injury, fire or property damage. Remember to give due consideration to safety when making your circuit designs, with appropriate measures such as (1) placement of substitutive, auxiliary, (2) use of non-flammable material or (3) prevention against any malfunction or mishap.

Notes regarding these materials

- These materials are intended as a reference to our customers in the selection of the ISAHAYA products best suited to the customer's application; they don't convey any license under any intellectual property rights, or any other rights, belonging ISAHAYA or third party.
- ISAHAYA Electronics Corporation assumes no responsibility for any damage, or infringement of any third party's rights, originating in the use of any product data, diagrams, charts or circuit application examples contained in these materials.
- All information contained in these materials, including product data, diagrams and charts, represent information on products at the time of publication of these materials, and are subject to change by ISAHAYA Electronics Corporation without notice due to product improvements or other reasons. It is therefore recommended that customers contact ISAHAYA Electronics Corporation or an authorized ISAHAYA products distributor for the latest product information before purchasing product listed herein.
- ISAHAYA Electronics Corporation products are not designed or manufactured for use in a device or system that is used under circumstances in which human life is potentially at stake. Please contact ISAHAYA Electronics Corporation or an authorized ISAHAYA products distributor when considering the use of a product contained herein for any specific purposes, such as apparatus or systems for transportation, vehicular, medical, aerospace, nuclear, or undersea repeater use.
- The prior written approval of ISAHAYA Electronics Corporation is necessary to reprint or reproduce in whole or in part these materials.
- If these products or technologies are subject to the Japanese export control restrictions, they must be exported under a license from the Japanese government and cannot be imported into a country other than the approved destination. Any diversion or re-export contrary to the export control laws and regulations of Japan and/or the country of destination is prohibited.
- Please contact ISAHAYA Electronics Corporation or authorized ISAHAYA products distributor for further details on these materials or the products contained therein.